



## LILIN JavaApplet SDK for IP Cameras

**Date:** 07/09/2013  
**Dept:** Technical Support, Taipei

**Subject:** How to use LILIN JavaApplet embedded in your HTML web page.

LILIN's iMEGAPRO and iMEGALITE series have one JavaApplet, LILINApplet, embedded in the cameras. LILINApplet is a cross-platform Applet for receiving video from LILIN IP camera. This Applet can work for Internet Explorer, Google Chrome, and FireFox. The JavaApplet also works for LILIN CMX, DVR 3 series, DVR 5 series, and NVR Touch series.

### The Source Code

If you are a developer, all you have to do is insert the following code into your web page.

```
<applet height="480" width="720" name="cvcs" archive=""/UniversalApplet.jar" codebase="http://59.124.49.26:60026"
code=" UniversalApplet.class" id="Applet1">
<param name="account" value="guest" />
<param name="password" value="guest" />
<param name="host" value="59.124.49.26" />
<param name="port" value="60022" />
</applet>
```


### Parameters

Account: account/user name of the IP camera

Password: password of the IP camera

Host: IP camera's IP address

Port: IP camera's HTTP port number, The default is at port 80.





## Public Surveillance

For some public surveillance such as on-line shopping, on-line museum, on-line pet store, and on-line sightseeing applications, to bypass authorization credential, please go to "Setup->User" on the IP camera via a browser. Enable "Bypass Logon" option to be On.

Once "Bypass Logon" option is On, there is no longer needed for login the cameras.



## For DVR, NVR, and CMX

For DVR, NVR, and CMX, LILINApplet is also used for HTTP port for connections. All you have to do is to use 6 lines of the source code for DVR, NVR, and CMX. LILINApplet switches to multi-view accordingly to the products.

For DVR and NVR, please use the code below by default.

```
<applet height="480" width="720" name="cvcs" archive="LilinApplet.jar" codebase="http://59.124.49.26:60022" code="LilinApplet.class" id="Applet1">
<param name="account" value="admin" />
<param name="password" value="1111" />
<param name="host" value="59.124.49.26" />
<param name="port" value="60022" />
</applet>
```

For CMX, please use the code below by default.

```
<applet height="480" width="720" name="cvcs" archive="LilinApplet.jar" codebase="http://59.124.49.26:60022" code="LilinApplet.class" id="Applet1">
<param name="account" value="admin" />
<param name="password" value="" />
<param name="host" value="59.124.49.26" />
<param name="port" value="60022" />
</applet>
```